


Linear Temperature Sensing Cable Termination Box



Overview

It is designed to effectively terminate up to two zones of FT-EN Linear Heat Detection cable in a secure, weatherproof enclosure. LHD Cable Accessory - Junction Box, IP65/66 w/ Cable Glands & Terminals ACA-JBW - ProReact A1343 The ACA-JBW junction box is designed to join and protect linear heat sensor cable against damage when cable joints are required. Approved to environmental. Digital Linear Heat Detector provides a very-early alarm detecting function to the protected environment, The detector can be known as an intelligent "switch" type detector. The polymers between the two conductors will break down at specific fixed temperature allowing the conductors contact, the. The SR-502 Series Junction Box Sealed Strain Relief Connector is used when the Protectowire Linear Heat Detector enters or exits the junction box. The EOL unit provides fault monitoring on the cable.



Article Content

Linear Heat Detection: LHD Cable Accessory

The ACA-JBW junction box is designed to join and protect linear heat sensor cable against damage when cable joints are required. The ACAJBW is weatherproof and is supplied with cable glands and ...

800 900 Series Linear Heat Detector (LHD)

The cable contains insulators which melt at a specific temperature. At the rated temperature, the heat sensitive polymeric insulation creates pressure between conductors, permitting them make contact ...

Junction Boxes and Feed Cable

Use as end-of-line box for CTM series modules. The SR-502 Series Junction Box Sealed Strain Relief Connector is used when the Protectowire Linear Heat Detector enters or exits the junction box. The ...

FW68 Fire Wire Linear Heat Sensing Cable Installation ...

FW68 Type E fire heat detector is a linear heat sensing cable consisting of a twin conductor cable with temperature sensitive insulation protected by a polythene braid. The cable must be used with the ...

Patol Analogue EOL Stainless Steel Termination Box ...

The 700-515 End of Line Junction Box in an attractive IP65 Stainless Steel finish has been designed to terminate cable on a Linear Heat Detection system.

End Of Line Terminators Linear Heat Detection Cable LHDC

It is suitable for the majority of applications and can be easily fixed in place. The Polycarbonate Junction Box is a basic method of jointing either Digital or Analogue LHDC and is supplied with two glands. It ...

Patol Analogue EOL Stainless Steel Termination Box with Fire & Fault ...

The 700-515 End of Line Junction Box in an attractive IP65 Stainless Steel finish has been designed to terminate cable on a Linear Heat Detection system.

Termination Unit_P.T. SECURITY TECHNOLOGY CO., LTD.

Termination Unit MS1000-P is used for Linear Heat Cable of MS1000 Conventional type, MS1000 CR/OD type and MS1000 EP type. It is used for balancing the signal status and with simulation ...

Signaline FT-EOL-EN Linear Heat Detector End of Line unit – Signaline

The Signaline FT-EOL-EN is a dual zone end of line termination unit for the Signaline FT-EN Linear Heat Detectors approved to EN54 part 28. It is designed to effectively terminate up to two zones of FT-EN ...

Linear Heat Detection Cable with Terminal Box

Digital Linear Heat Detector provides a very-early alarm detecting function to the protected environment, The detector can be known as an intelligent "switch" type ...

SC RG Junction and Termination Boxes

The J/ELR Box is a nonmetallic junction and termination box which is UL listed with a NEMA 4X rating and manufactured from PVC or PPO thermoplastic. A foam-in-place gasketed lids attaches with ...

Linear Heat Detection Installation Manual

In order to hold the SafeCable securely in place, and provide a dust and moisture free environment in the junction and termination boxes, a Strain Relief Connector (Part #: TC100 - Figure 21) must be ...

S200XA Linear Heat Series Sensor Cables

These special linear heat sensor cables are suited for indoor and outdoor use. Each cable includes two MM fibers for temperature sensing. These sensor cables have a halogen-free and flame-retardant ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.sdesign.net.pl>

Email: sales@sdesign.net.pl

Phone: +48 694 237 815

Address: ul. Marszałkowska 10, 00-001 Warsaw, Poland

This document is for informational purposes only. Specifications subject to change without notice.

